

Publikationen Dr.-Ing. Bernd Wetzel

Stand: Januar 2024

Buchbeiträge

- [1] J. Hausmann, J. Krummenacker, A. Klingler und B. Wetzel, „Improvement of fatigue strength of carbon fiber reinforced polymers by matrix modifications for ultrafast rotating flywheels“ in: *Frontiers of Science and Technology*, de Gruyter, 2021, S. 279–289, doi: 10.1515/9783110584455-018.
- [2] E. I. Akpan, X. Shen, B. Wetzel und K. Friedrich, „Design and synthesis of polymer nanocomposites“ in *Polymer Composites with Functionalized Nanoparticles*, Elsevier, 2019, S. 47–83, doi: 10.1016/b978-0-12-814064-2.00002-0.
- [3] F. Hauptert und B. Wetzel, „Reinforcement of Thermosetting Polymers by the Incorporation of Micro- and Nanoparticles“ in *Polymer Composites*, Boston, MA.: Springer-Verlag, S. 45–62, doi: 10.1007/0-387-26213-x_3.
- [4] S. Komatsu, B. Wetzel und K. Friedrich, „Novel Liquid Crystal Polymers with Tailored Chemical Structure for High Barrier, Mechanical and Tribological Performance“ in *Liquid Crystalline Polymers*, S. 15–39, doi: 10.1007/978-3-319-20270-9_2.

Fachkonferenzen

- [5] J.-K. Krüger, B. Wetzel, und A. Klingler, „The Topology Freezing Phenomenon of Vitrimers as Seen by Static and Dynamic Thermo-Physical Properties“, gehalten auf der 16th International Conference on Advanced Computational Engineering and Experimenting (ACEX2023), Heraklion, Griechenland, 3. Juli 2023.
- [6] A. Klingler, B. Wetzel, und J.-K. Krüger, „Vitriemer phase transitions from the perspective of ultra-slow volume changes“, gehalten auf der EUPOC 2023, Bertinoro, Italy, 14. Mai 2023.
- [7] B. Wetzel, „Properties of delignified compacted wood“, Polytrib 2022, Stockholm, Schweden, 5. Dezember 2022
- [8] M. Gilberg, J.-K. Krüger und B. Wetzel, „Determination of Polymerization-Induced Volume Changes of UV-Curable Resins via TMOR“, Poly-Char 2022, 23. Mai 2022
- [9] A. Klingler; Q. He; L. Ye; U. Breuer; K. Friedrich und B. Wetzel, „Damage resistance of thin and tough carbon fibre reinforced epoxy“, 1st Virtual ESIS-TC4 Conference on Fracture of Polymers, Composites and Adhesives, 28.-29.09.2021
- [10] M. Gilberg, J.K. Krüger und B. Wetzel, „Investigation of shrinkage-optimized resin via TMOR“, *Virtual European Symposium of Photopolymer Sciences (vESPS)*, virtual conference, June 2021
- [11] X. Shen, E. Padenko, B. Wetzel und K. Friedrich, „Bioinspired graphene/liquid crystalline polymer nanocomposite coatings for tribological applications“, *22nd International Conference on Composite Melbourne*, 2019.
- [12] J. Krummenacker, J. Hausmann, L. Sorochynska, A. Klingler und B. Wetzel, „Development of a cyclic test method for ultra-fast rotating flywheels made of CFRP and improvement of their fatigue

strength by matrix modifications“, *21st International Conference on Composite Materials Xi'an 2025th August, 2017*.

- [13] M. Kopietz, S. Grishchuk und B. Wetzel, „Innovative phosphate-free alternatives for silicate resins applied in sewer rehabilitation“, *32nd International Conference, Lyon, 2016*, doi: 10.1063/1.5016733.
- [14] F. Rieger *et al.*, „Induction welding of carbon fiber reinforced thermoset composites via thermoplastics: overview of experimental analysis of induction welded single-lap joints“, *ECCM 17 Munich, 2016*.
- [15] B. Wetzel, F. Oster und F. Hauptert, „Nanoparticle filled polymers: manufacturing, structure, properties“ in *SKZ-Fachtagung, 2004*.

Fachzeitschriften

- [12] A. Klingler, M. Gilberg, D. Reisinger, S. Schlögl, B. Wetzel, und J.-K. Krüger, „Thermal volume expansion as seen by Temperature-modulated optical refractometry, Oscillating dilatometry and Thermo-mechanical analysis“, *Polymer Testing*, Bd. 131, S. 108340, Feb. 2024, doi: 10.1016/j.polymertesting.2024.108340.
- [13] Y. Lin, R. He, Y. Xu, J. Zhang, B. Wetzel, und G. Zhang, „Significance of nickel particles on reducing friction and wear of polyimide subjected to harsh boundary lubrication conditions“, *Tribology International*, Nr. 178, Nov. 2022, doi: <https://doi.org/10.1016/j.triboint.2022.108063>
- [14] A. Klingler, Q. He, B. Wetzel, T. Allen, L. Ye, und U. Breuer, „Low velocity impact resistance of thin and toughened carbon fibre reinforced epoxy“, *Composites Science and Technology*, S. 109362, Feb. 2022, doi: 10.1016/j.compscitech.2022.109362.
- [15] A. Klingler, M. Gilberg, B. Wetzel, U. Breuer, und J.-K. Krüger, „Temperature-rate induced polymerization and phase separation of block copolymer toughened polymer composites“, *Composites Science and Technology*, S. 109329, Feb. 2022, doi: 10.1016/j.compscitech.2022.109329.
- [16] A. Klingler, M. Gilberg, B. Wetzel und J.-K. Krüger, „Simultaneous access to different types of volume changes and the degree of cure during isothermal polymerization of polymer networks“, *Express Polym. Lett.*, Bd. 16, Nr. 11, S. 1193–1207, 2022, doi: 10.3144/expresspolymlett.2022.87.
- [17] A. Klingler, M. Gilberg, J.-K. Krüger und B. Wetzel, „On volume changes during homopolymerization of polymer networks accessed via “Temperature modulated optical refractometry”“, *Thermochimica Acta*, Bd. 711, S. 179185, Mai 2022, doi: 10.1016/j.tca.2022.179185.
- [18] S. Grzesiak, M. Pahn, A. Klingler, E. Akpan, M. Schultz-Cornelius und B. Wetzel, „Mechanical and Thermal Properties of Basalt Fibre Reinforced Polymer Lamellas for Renovation of Concrete Structures“, *Polymers*, Jg. 14, Nr. 4, S. 790, 2022, doi: 10.3390/polym14040790.
- [19] A. Klingler, M. Gilberg, J.-K. Krüger und B. Wetzel, „On volume changes during homopolymerization of polymer networks accessed via “Temperature modulated optical refractometry”“, *Thermochimica Acta*, Jg. 711, S. 179185, 2022, doi: 10.1016/j.tca.2022.179185.
- [20] A. Klingler, M. Gilberg, B. Wetzel, U. Breuer und J.-K. Krüger, „Temperature-rate induced polymerization and phase separation of block copolymer toughened polymer composites“, *Composites Science and Technology*, S. 109329, 2022, doi: 10.1016/j.compscitech.2022.109329.
- [21] A. Klingler, Q. He, B. Wetzel, T. Allen, L. Ye und U. Breuer, „Low velocity impact resistance of thin and toughened carbon fibre reinforced epoxy“, *Composites Science and Technology*, S. 109362, 2022, doi: 10.1016/j.compscitech.2022.109362.
- [22] E. Akpan, K. Friedrich, S. Jacob, E. Thines und B. Wetzel, „Reactive Layer Assembly Sustains an

- Interlocked Structure in Green Processed and Scalable High-Performance Layered Wood“, *ACS Sustainable Chemistry & Engineering*, 2021, doi: 10.1021/acssuschemeng.1c03468.
- [23] E. Akpan, B. Wetzel und K. Friedrich, „Eco-friendly and Sustainable Processing of Wood Based Materials“, *Green Chemistry*, 2021, doi: 10.1039/D0GC04430J.
- [24] K. Friedrich, E. I. Akpan und B. Wetzel, „On the tribological properties of extremely different wood materials“, *Eur. J. Wood Prod. (European Journal of Wood and Wood Products)*, 2021, doi: 10.1007/s00107-020-01654-2.
- [25] E. I. Akpan, B. Wetzel und K. Friedrich, „Process design for performance improvement in purely ecofriendly composites for structural applications“, *J Appl Polym Sci (Journal of Applied Polymer Science)*, Jg. 137, Nr. 21, S. 48719, 2020, doi: 10.1002/app.48719.
- [26] M. Kopietz, K. Friedrich und B. Wetzel, „In situ functionalisation of organomineral hybrid resins for tough basalt fibre reinforced plastics“, *Plastics, Rubber and Composites*, Jg. 50, Nr. 3, S. 105–115, 2020, doi: 10.1080/14658011.2020.1840202.
- [27] A. Bajpai, B. Wetzel und K. Friedrich, „High strength epoxy system modified with soft block copolymer and stiff core-shell rubber nanoparticles: Morphology, mechanical properties, and fracture mechanisms“, *Express Polymer Letters*, Jg. 14, Nr. 4, S. 384–399, 2020, doi: 10.3144/expresspolymlett.2020.32.
- [28] M. Ornelas *et al.*, „Use of biogenic silica nanoparticles derived from biomass in polymeric formulations and their applications“, *AEMAC*, Jg. 4, Nr. 3, S. 22–28, 2020.
- [29] A. Bajpai und B. Wetzel, „Effect of Different Types of Block Copolymers on Morphology, Mechanical Properties, and Fracture Mechanisms of Bisphenol-F Based Epoxy System“, *Journal of Composites Science*, Jg. 3, Nr. 3, S. 68, 2019, doi: 10.3390/jcs3030068.
- [30] A. Bajpai und B. Wetzel, „Tensile Testing of Epoxy-Based Thermoset System Prepared by Different Methods“, 2019, doi: 10.20944/preprints201907.0143.v1.
- [31] A. Bajpai, B. Wetzel, A. Klingler und K. Friedrich, „Mechanical properties and fracture behavior of high-performance epoxy nanocomposites modified with block polymer and core-shell rubber particles“, *Journal of Applied Polymer Science*, Jg. 137, Nr. 11, S. 48471, 2019, doi: 10.1002/app.48471.
- [32] A. Bajpai, B. Wetzel, A. Klingler und K. Friedrich, „Mechanical properties and fracture behavior of high-performance epoxy nanocomposites modified with block polymer and core-shell rubber particles“, *Journal of Applied Polymer Science*, Jg. 137, Nr. 11, S. 48471, 2019, doi: 10.1002/app.48471.
- [33] Goergen *et al.*, „Novel Approach in B-Staging of an Epoxy Resin for Development of rCF NonWoven Prepregs for RTP Processing“, *Key Engineering Materials*, Jg. 809, S. 521–526, 2019, doi: 10.4028/www.scientific.net/KEM.809.521.
- [34] M. Kopietz, B. Wetzel und K. Friedrich, „Flexural and fracture mechanical properties of in situ particulate reinforced organomineral hybrid resins modified by organofunctional silanes“, *Composites Science and Technology*, Jg. 174, S. 169–175, 2019.
- [35] E. I. Akpan, B. Wetzel und K. Friedrich, „A fully biobased tribology material based on acrylic resin and short wood fibres“, *Tribology International*, Jg. 120, S. 381–390, 2018.
- [36] A. Bajpai, A. Alapati, A. Klingler und B. Wetzel, „Tensile properties, fracture mechanics properties and toughening mechanisms of epoxy systems modified with soft block copolymers, rigid TiO₂ nanoparticles and their hybrids“, *Journal of Composites Science*, Jg. 2, Nr. 4, S. 72, 2018, doi: 10.3390/jcs2040072.
- [37] K. Friedrich, E. I. Akpan und B. Wetzel, „Sliding wear performance of dry and oil impregnated black-fiber palm wood“, *Jurnal Tribologi*, Jg. 16, S. 51–70, 2018.
- [38] A. Klingler und B. Wetzel, „The effect of block copolymer and core-shell rubber hybrid toughening on morphology and fracture of epoxy-based fibre reinforced composites“, *Engineering Fracture Mechanics*, Jg. 203, Nr. 2, S. 81–101, 2018, doi: 10.1016/j.engfracmech.2018.06.044.

- [39] M. Kopietz und B. Wetzel, „Impact of aggressive media on the interlaminar shear strength of innovative glass fiber reinforced polyurea/polysilicate hybrid resins“, *Procedia Structural Integrity*, Jg. 13, S. 143–148, 2018, doi: 10.1016/j.prostr.2018.12.024.
- [40] E. I. Akpan, B. Wetzel und K. Friedrich, „Processing and properties of short wood fiber/acrylate resin composites“, *Polymer Composites*, Jg. 40, Nr. 1, S. 91–98, 2017.
- [41] E. I. Akpan, B. Wetzel und K. Friedrich, „Processing and properties of short wood fiber/acrylate resin composites“, *Polymer Composites*, Jg. 40, Nr. 1, S. 91–98, 2017, doi: 10.1002/pc.24604.
- [42] K. Friedrich, E. I. Akpan und B. Wetzel, „Structure and mechanical/abrasive wear behavior of a purely natural composite: black-fiber palm wood“, *Journal of Materials Science*, Jg. 52, Nr. 17, S. 10217–10229, 2017, doi: 10.1007/s10853-017-1184-5.
- [43] A. Klingler, L. Sorochynska und B. Wetzel, „Toughening of glass fiber reinforced unsaturated polyester composites by core-shell particles“, *Key Engineering Materials*, Jg. 742, S. 74–81, 2017.
- [44] A. Klingler und B. Wetzel, „Fatigue Crack Propagation in Triblock Copolymer Toughened Epoxy Nanocomposites“, *Polymer Engineering and Science*, 2017.
- [45] M. Kopietz, F. Bilgin, S. Grishchuk und B. Wetzel, „Fiber/Matrix Adhesion in Glass Fiber Reinforced Inorganic-Organic Polyurea/Polysilicate Resins“, *Key Engineering Materials*, Jg. 742, S. 9–16, 2017.
- [46] A. Bajpai, A. K. Alapati und B. Wetzel, „Toughening and mechanical properties of epoxy modified with block co-polymers and MWCNTs“, *Procedia Structural Integrity*, Jg. 2, S. 104–111, 2016, doi: 10.1016/j.prostr.2016.06.014.
- [47] A. Bajpai, A. K. Alapati und B. Wetzel, „Toughening and Mechanical Properties of Epoxy Modified with Block Co-polymers and MWCNTs“, *Procedia Structural Integrity*, Jg. 2, S. 104–111, 2016.
- [48] Dmitriev, I. Häusler, W. Österle, B. Wetzel und G. Zhang, „Modeling of the stress\textendashstrain behavior of an epoxy-based nanocomposite filled with silica nanoparticles“, *Materials & Design*, Jg. 89, S. 950–956, 2016.
- [49] C.P. Gao *et al.*, „Tribological behaviors of epoxy composites under water lubrication conditions“, *Tribology International*, Jg. 95, S. 333–341, 2016.
- [50] W. Österle *et al.*, „The role of carbon fibers and silica nanoparticles on friction and wear reduction of an advanced polymer matrix composite“, *Materials & Design*, Jg. 93, S. 474–484, 2016, doi: 10.1016/j.matdes.2015.12.175.
- [51] E. Padenko, L.J. van Rooyen, B. Wetzel und J. Karger-Kocsis, „Ultralow sliding wear polytetrafluoro ethylene nanocomposites with functionalized graphene“, *Journal of Reinforced Plastics and Composites*, Jg. 35, Nr. 11, S. 892–901, 2016, doi: 10.1177/0731684416630817.
- [52] H. Qi *et al.*, „Exploring the influence of counterpart materials on tribological behaviors of epoxy composites“, *Tribology International*, Jg. 103, S. 566–573, 2016.
- [53] G. Zhang *et al.*, „The role of surface topography in the evolving microstructure and functionality of tribofilms of an epoxy-based nanocomposite“, *Wear*, 364-365, S. 48–56, 2016.
- [54] L. Zhang *et al.*, „Distinct tribological mechanisms of silica nanoparticles in epoxy composites reinforced with carbon nanotubes, carbon fibers and glass fibers“, *Tribology International*, Jg. 104, S. 225–236, 2016.
- [55] F. Zhao *et al.*, „Tribological behaviors of carbon fiber reinforced epoxy composites under PAO lubrication conditions“, *Tribology Letters*, Jg. 62, Nr. 3, 2016, doi: 10.1007/s11249-016-0685-8.
- [56] Dmitriev, W. Österle, B. Wetzel und G. Zhang, „Mesoscale modeling of the mechanical and tribological behavior of a polymer matrix composite based on epoxy and 6vol.% silica nanoparticles“, *Computational Materials Science*, Jg. 110, S. 204–214, 2015.
- [57] W. Österle *et al.*, „Exploring the beneficial role of tribofilms formed from an epoxy-based hybrid nanocomposite“, *Tribology International*, Jg. 88, S. 126–134, 2015.

- [58] W. Österle *et al.*, „Exploring the potential of Raman spectroscopy for the identification of silicone oil residue and wear scar characterization for the assessment of tribofilm functionality“, *Tribology International*, Jg. 90, S. 481–490, 2015.
- [59] E. Padenko, P. Berki, B. Wetzel und J. Karger-Kocsis, „Mechanical and abrasion wear properties of hydrogenated nitrile butadiene rubber of identical hardness filled with carbon black and silica“, *Journal of Reinforced Plastics and Composites*, Jg. 35, Nr. 1, S. 81–91, 2015.
- [60] S. Sharma, E. Padenko, J. Bijwe, B. Wetzel und K. Friedrich, „Erosive and sliding wear of polybenzimidazole at elevated temperatures“, *Journal of Materials Science*, Jg. 51, Nr. 1, S. 262–270, 2015.
- [61] G. Zhang, I. Häusler, W. Österle, B. Wetzel und B. C. Jim, „Formation and function mechanisms of nanostructured tribofilms of epoxy-based hybrid nanocomposites“, *Wear*, 342-343, S. 181–188, 2015.
- [62] G. Zhang, B. Wetzel, B. C. Jim und W. Oesterle, „Impact of counterface topography on the formation mechanisms of nanostructured tribofilm of PEEK hybrid nanocomposites“, *Tribology International*, Jg. 83, S. 156–165, 2015.
- [63] G. Zhang, B. Wetzel und Q. H. Wang, „Tribological behavior of PEEK-based materials under mixed and boundary lubrication conditions“, *Tribology International*, Jg. 88, S. 153–161, 2015.
- [64] Almajid, L. Soroehyńska, K. Friedrich und B. Wetzel, „Effects of graphene and CNT on mechanical, thermal, electrical and corrosion properties of vinylester based nanocomposites“, *Plastics, Rubber and Composites*, Jg. 44, Nr. 2, S. 50–62, 2014.
- [65] S. Grishchuk *et al.*, „Toward reliable morphology assessment of thermosets via physical etching: Vinyl ester resin as an example“, *Express Polymer Letters*, Jg. 7, Nr. 5, S. 407–415, 2013.
- [66] M. Marquart *et al.*, „Enhancing the lifetime of MoS₂-lubricated ball bearings“, *Wear*, Jg. 303, 1-2, S. 169–177, 2013.
- [67] R. Sebastian, A. Noll, G. Zhang, T. Burkhart und B. Wetzel, „Friction and wear of PPS/CNT nanocomposites with formation of electrically isolating transfer films“, *Tribology International*, Jg. 64, S. 187–195, 2013.
- [68] G. Zhang, T. Burkhart und B. Wetzel, „Tribological behavior of epoxy composites under diesellubricated conditions“, *Wear*, Jg. 307, 1-2, S. 174–181, 2013.
- [69] D. Y. Zhu, B. Wetzel, A. Noll, M. Z. Rong und M. Q. Zhang, „Thermo-molded self-healing thermoplastics containing multilayer microreactors“, *Journal of Materials Chemistry A*, Jg. 1, Nr. 24, S. 7191, 2013.
- [70] M. Philipp *et al.*, „Effect of mixing sequence on the curing of amine-hardened epoxy/ alumina nanocomposites as assessed by optical refractometry“, *Express Polymer Letters*, Jg. 2, Nr. 8, S. 546–552, 2008.
- [71] M. Philipp *et al.*, „The impact of specific nanoparticle-reactant interactions on the physical properties of thermosets: epoxy/alumina nanocomposites“, *Express Polymer Letters*, XY, Nr. 8, S. 546–552, 2008.
- [72] Hallouet, B. Wetzel und R. Pelster, „On the Dielectric and Magnetic Properties of Nanocomposites“, *Journal of Nanomaterials*, Jg. 2007, S. 1–11, 2007.
- [73] R. Sanctuary *et al.*, „Complex specific heat capacity of two nanocomposite systems“, *Thermochimica Acta*, Jg. 445, Nr. 2, S. 111–115, 2006, doi: 10.1016/j.tca.2005.05.024.
- [74] Wetzel, P. Rosso, F. Hauptert und K. Friedrich, „Epoxy nanocomposites - fracture and toughening mechanisms“, *Engineering Fracture Mechanics*, Jg. 73, S. 2375–2398, 2006, doi: 10.1016/j.engfracmech.2006.05.018.
- [75] Q.L. Ji, M. Q. Zhang, M. Z. Rong, B. Wetzel und K. Friedrich, „Friction and wear of epoxy composites containing surface modified SiC nanoparticles“, *Tribology Letters*, Jg. 2, S. 115–123, 2005.

- [76] J. K. Krueger *et al.*, „The generalized Cauchy relation as an universal property of the amorphous state“, *Journal of Physics IV (Proceedings)*, Jg. 129, Nr. 2, S. 45–49, 2005, doi: 10.1051/jp4:2005129010.
- [77] K. Friedrich, T. Goda, K. Varady und B. Wetzel, „Finite element simulation of the fiber/matrix debonding in polymer composites produced by a sliding indenter: part I - normally oriented fibers“, *Journal of Composite Materials*, Jg. 38, S. 1583–1606, 2004.
- [78] T. Goda, K. Varady, B. Wetzel und K. Friedrich, „Finite element simulation of the fiber/matrix debonding in polymer composites produced by a sliding indenter: part II - parallel and anti-parallel fiber orientation“, *Journal of Composite Materials*, Jg. 38, S. 1607–1618, 2004.
- [79] Q.L. Ji, M. Q. Zhang, M. Z. Rong, B. Wetzel und K. Friedrich, „Tribological properties of nanosized silicon carbide filled epoxy composites“, *Acta Materiae Compositae Sinica*, Jg. 256, S. 1072–1081, 2004.
- [80] Q.L. Ji, M. Q. Zhang, M. Z. Rong, B. Wetzel und K. Friedrich, „Tribological properties of surface modified nano-alumina/epoxy composites“, *Journal of Materials Science*, Jg. 256, S. 1072–1081, 2004.
- [81] J. Lu *et al.*, „Thermal stability of frictional surface layer and wear debris of epoxy nanocomposites in relation to the mechanism of tribological performance improvement“, *Journal of Materials Science*, Jg. 29, S. 3817–3820, 2004.
- [82] G. Shi, M. Q. Zhang, M. Z. Rong, B. Wetzel und K. Friedrich, „Sliding wear behavior of epoxy containing nano- Al_2O_3 particles with different pretreatments“, *Wear*, Jg. 256, S. 1072–1081, 2004.
- [83] M. Z. Rong *et al.*, „Graft polymerisation onto inorganic nanoparticles and its effect on tribological performance improvement of polymer composites“, *Tribology International*, Jg. 36, S. 697–707, 2003.
- [84] G. Shi, M. Q. Zhang, M. Z. Rong, B. Wetzel und K. Friedrich, „Friction and wear of low nanometer Si_3N_4 filled epoxy composites“, *Wear*, Jg. 254, S. 784–796, 2003.
- [85] Wetzel, F. Hauptert und M. Q. Zhang, „Epoxy nanocomposites with high mechanical and tribological performance“, *Composite Science and Technology*, Jg. 63, S. 2055–2067, 2003, doi: 10.1016/S0266-3538(03)00115-5.
- [86] Wetzel, F. Hauptert, K. Friedrich, M. Q. Zhang und M. Z. Rong, „Impact and wear resistance of polymer nanocomposites at low filler content“, *Polymer Engineering and Science*, Jg. 53, Nr. 2, S. 72–77, 2002, doi: 10.1002/pen.11084.
- [87] M. Q. Zhang, M. Z. Rong, L.Y. Shu, B. Wetzel und K. Friedrich, „Effect of particle surface treatment on the tribological performance of epoxy based nanocomposites“, *Wear*, Jg. 253, S. 1086–1093, 2002.
- [88] M. Q. Zhang, M. Z. Rong, S.L. Yu, B. Wetzel und K. Friedrich, „Improvement of the tribological performance of epoxy by the addition of irradiation grafted nano-inorganic particles“, *Macromolecular Materials Engineering*, Jg. 287, Nr. 2, S. 111–115, 2002.
- [89] M. Z. Rong *et al.*, „Microstructure and tribological behavior of polymeric nanocomposites“, *Industrial Lubrication and Tribology*, Jg. 53, Nr. 2, S. 72–77, 2001.
- [90] M. Q. Zhang *et al.*, „Atomic force microscopy study on structure and properties of irradiation grafted silica particles in polypropylene-based nanocomposites“, *Journal of Applied Polymer Science*, Jg. 80, S. 2218–2227, 2001.